

LCF3-Motorized Comparison Microscope

Leeds LCF3-Motorized firearms comparison microscope features **3-axis motorized stages**.

Built with **Olympus optics**, the LCF3-M offers a 16:1 zoom ratio and built-in aperture diaphragms, providing examiners with 14 matched magnification positions to choose from.

The optical bridge produces an erect, un-reversed image with a 22mm field of view.

Incorporating several ergonomic design features, the LCF3-M can be adjusted to meet the needs of examiners at various heights. Leeds **universal holders** eliminate the need for multiple sample holders and accessory brushes.

The LCF3-M offers an assortment of **lighting options** -- including Leeds

- Quad lamp fluorescent lighting,
- Gooseneck bifurcated fiber optic light guide with spot lens,
- LED Cube Illuminator fiber



Designed with two 9" x 7" freestanding platform stages, the LCF3-M allows an examiner to easily access the work area from all sides, accommodating larger articles of evidence for analysis.

Optional controllers for the LCF3-M stages:

Trackball Mouse





HID controller

LCF3-Motorized Specifications

	<u> </u>		
<u>Objective</u>	<u>1.0x*</u>	<u>0.5x</u>	<u>1.6x</u>
Zoom Range	6 - 102x	3.0 - 51x	9.6 - 163.2x
Working Distance (mm)	60	70.5	30
	0.15	0.075	0.24
	* 1x objective is most commonly used for zoom range		
Matched magnification positions	6, 7, 9, 11, 14, 18, 22, 28,		
with 1x objective	36, 45, 56, 71, 89, 102x		
Zoom Ratio	16:1		
Field Number (mm)	22		
Stage Movement & Universal	X-axis (mm)		95
Holder	Y-axis (mm)		95
	Z-axis (mm)		42
Axial Slo			90°
	Axial Rotation Base Rotation Stage Size (mm)		360°
			360°
			177 x 228
Universal Holder	Outside Diameter		0.030 - 0.78"
	Inside Diameter		0.36 - 1.12"
Micrometer Range	Range		0 - 3"/0-75mm
	Resolution		0.0005"/0.01mm
Table Dimensions	Height (Standard Leg)		26" - 38"
	Height (Short Leg)		24" - 34"
	Width		35.5"
	Depth		24"
	Footprint		35.5" x 24"
Station Coumn Z-Axis	Vertical Travel		6"
Electrical Requirements	Voltage		100 - 240 VAC
	Current (max)		15 A
	Frequency		50 - 60 Hz



LEEDS PRECISION INSTRUMENTS, INC. DBA LEEDS FORENSIC SYSTEMS

17300 Medina Road, Suite 600, Minneapolis MN 55447 USA 763.546.8575 // WWW.LEEDSMICRO.COM